

Gewichtstabelle für Stahlrohre bis 9,5 mm Wandstärke

Ø	Wandstärke in mm										
	3.6	4.0	4.5	5.0	5.6	5.9	6.3	7.1	8.0	8.8	9.5
48.3	4.0	4.4	4.9	5.3	5.9	6.2	6.5	7.2	7.9	8.6	9.1
60.3	5.0	5.6	6.2	6.8	7.6	7.9	8.4	9.3	10.3	11.2	11.9
70	5.9	6.5	7.3	8.0	8.9	9.3	9.9	11.0	12.2	13.3	14.2
73	6.2	6.8	7.6	8.4	9.3	9.8	10.4	11.5	12.8	13.9	14.9
76.1	6.4	7.1	7.9	8.8	9.7	10.2	10.8	12.1	13.4	14.6	15.6
82.5	7.0	7.7	8.7	9.6	10.6	11.1	11.8	13.2	14.7	16.0	17.1
88.9	7.6	8.4	9.4	10.3	11.5	12.1	12.8	14.3	16.0	17.4	18.6
95	8.1	9.0	10.0	11.1	12.3	13.0	13.8	15.4	17.2	18.7	20.0
101.6	8.7	9.6	10.8	11.9	13.3	13.9	14.8	16.5	18.5	20.1	21.6
108	9.3	10.3	11.5	12.7	14.1	14.8	15.8	17.7	19.7	21.5	23.1
114.3	9.8	10.9	12.2	13.5	15.0	15.8	16.8	18.8	21.0	22.9	24.5
121	10.4	11.5	12.9	14.3	15.9	16.7	17.8	19.9	22.3	24.3	26.1
127	11.0	12.1	13.6	15.0	16.8	17.6	18.7	21.0	23.5	25.6	27.5
133	11.5	12.7	14.3	15.8	17.6	18.5	19.7	22.0	24.6	26.9	28.9
139.7	12.1	13.4	15.0	16.6	18.5	19.5	20.7	23.2	26.0	28.4	30.5
146	12.6	14.0	15.7	17.4	19.4	20.4	21.7	24.3	27.2	29.8	32.0
152.4	13.2	14.6	16.4	18.2	20.3	21.3	22.7	25.4	28.5	31.1	33.5
159	13.8	15.3	17.1	19.0	21.2	22.3	23.7	26.6	29.8	32.6	35.0
168.3	14.6	16.2	18.2	20.1	22.5	23.6	25.2	28.2	31.6	34.6	37.2
177.8	15.5	17.1	19.2	21.3	23.8	25.0	26.6	29.9	33.5	36.7	39.4
193.7	16.9	18.7	21.0	23.3	26.0	27.3	29.1	32.7	36.6	40.1	43.1
203	17.7	19.6	22.0	24.4	27.2	28.7	30.5	34.3	38.5	42.1	45.3
219.1	19.1	21.2	23.8	26.4	29.5	31.0	33.0	37.1	41.6	45.6	49.1
229		22.2	24.9	27.6	30.8	32.4	34.6	38.8	43.6	47.8	51.4
244.5		23.7	26.6	29.5	33.0	34.7	37.0	41.5	46.6	51.1	55.0
273		26.5	29.8	33.0	36.9	38.8	41.4	46.5	52.3	57.3	61.7
298.5		29.0	32.6	36.2	40.4	42.6	45.4	51.0	57.3	62.8	67.7
323.9		31.5	35.4	39.3	43.9	46.2	49.3	55.4	62.3	68.3	73.6
339.7				41.3	46.1	48.5	51.8	58.2	65.4	71.8	77.3
355.6				43.2	48.3	50.9	54.2	61.0	68.5	75.2	81.0
406.4				49.5	55.3	58.2	62.1	69.9	78.6	86.2	92.9
457.2				55.7	62.3	65.6	70.0	78.8	88.6	97.3	105
508				62.0	69.3	73.0	77.9	87.7	98.6	108	117
609.6					83.4	87.8	93.7	105	119	130	141
Ø	3.6	4.0	4.5	5.0	5.6	5.9	6.3	7.1	8.0	8.8	9.5

Gewichtstabelle für Stahlrohre ab 10,0 mm Wandstärke

Ø	Wandstärke in mm									
	10.0	11.0	12.5	14.2	16.0	17.5	20.0	22.2	25.0	30.0
48.3	9.4	10.1	11.0							
60.3	12.4	13.4	14.7	16.1	17.5					
70	14.8	16.0	17.7	19.5	21.3	22.6	24.6			
73	15.5	16.8	18.6	20.6	22.5	23.9	26.1			
76.1	16.3	17.7	19.6	21.7	23.7	25.3	27.7			
82.5	17.9	19.4	21.6	23.9	26.2	28.0	30.8	33.0	35.4	
88.9	19.4	21.1	23.5	26.1	28.8	30.8	34.0	36.5	39.4	
95	21.0	22.8	25.4	28.3	31.2	33.4	37.0	39.8	43.1	
101.6	22.6	24.6	27.5	30.6	33.8	36.3	40.2	43.4	47.2	52.9
108	24.2	26.3	29.4	32.8	36.3	39.0	43.4	47.0	51.1	57.7
114.3	25.7	28.0	31.4	35.0	38.8	41.8	46.5	50.4	55.0	62.3
121	27.4	29.8	33.4	37.4	41.4	44.6	49.8	54.1	59.2	67.3
127	28.8	31.5	35.3	39.5	43.8	47.2	52.7	57.3	62.9	71.7
133	30.3	33.1	37.1	41.6	46.1	49.8	55.7	60.6	66.6	76.2
139.7	32.0	34.9	39.2	43.9	48.8	52.7	59.0	64.3	70.7	81.1
146	33.5	36.6	41.1	46.1	51.3	55.4	62.1	67.7	74.6	85.8
152.4	35.1	38.3	43.1	48.4	53.8	58.2	65.3	71.2	78.5	90.5
159	36.7	40.1	45.1	50.7	56.4	61.0	68.5	74.9	82.6	95.4
168.3	39.0	42.7	48.0	53.9	60.1	65.0	73.1	79.9	88.3	102
177.8	41.4	45.2	50.9	57.3	63.8	69.1	77.8	85.1	94.2	109
193.7	45.3	49.5	55.8	62.8	70.1	76.0	85.6	93.8	104	121
203	47.6	52.1	58.7	66.1	73.7	80.0	90.2	98.9	110	128
219.1	51.5	56.4	63.7	71.7	80.1	87.0	98.2	108	120	140
229	54.0	59.1	66.7	75.2	84.0	91.2	103	113	126	147
244.5	57.8	63.3	71.5	80.6	90.1	97.9	111	122	135	159
273	64.8	71.0	80.3	90.6	101	110	125	137	153	180
298.5	71.1	78.0	88.1	99.5	111	121	137	151	169	199
323.9	77.4	84.8	95.9	108	121	132	150	165	184	217
339.7	81.3	89.1	101	114	128	139	158	174	194	229
355.6	85.2	93.4	106	119	134	146	165	182	204	241
406.4	97.7	107	121	137	154	168	190	210	235	278
457.2	110	121	137	155	174	190	216	238	266	316
508	123	135	153	173	194	212	241	266	298	353
609.6	148	162	184	208	234	255	291	321	360	429
Ø	10.0	11.0	12.5	14.2	16.0	17.5	20.0	22.2	25.0	30.0