

Kernrohre T2 – T6 - T6tr Triple – T 6 S

Technische Daten und Empfehlungen

Hartmetal Kronen

Daten					Empfehlungen		
Typ	Bohr Ø mm	Kern Ø mm	Aussenrohr Ø mm	Gewicht Kernrohr Kg	Vorschubkraft kN	Wassermenge l/Min	Drehzahl U/Min
T2 – 46 - 1500	46,5	31,7	45,2	13	14 / 17	5 / 7	750 / 1250
T2 – 46 – 3000				22			
T2 – 56 - 1500	56,5	41,7	55,2	14	13 / 20	6 / 9	600 / 1000
T2 – 56 – 3000				23			
T2 – 66 – 1500	66,5	51,7	65,2	18	17 / 24	12 / 20	500 / 850
T2 – 66 – 3000				29			
T2 – 76 – 1500	76,5	61,7	75,2	21	19 / 29	21 / 35	450 / 750
T2 – 76 – 3000				34			
T2 – 86 – 1500	86,5	71,7	85,2	26	22 / 32	35 / 60	390 / 660
T2 – 86 – 3000				41			
T2 – 101 – 1500	101,5	83,7	99,0	38	31 / 45	74 / 118	330 / 570
T2 – 101 – 3000				59			

Daten					Empfehlungen		
Typ	Bohr Ø mm	Kern Ø mm	Aussenrohr Ø mm	Gewicht Kernrohr Kg	Vorschubkraft kN	Wassermenge l/Min	Drehzahl U/Min
T6 – 101 – 1500	101,3	79,0	98,2	46	30 / 45	67 / 94	300 / 550
T6 – 101 – 3000				69			
T6 – 116 – 1500	116,3	93,0	113,0	59	37 / 55	109 / 152	280 / 480
T6 – 116 – 3000				86			
T6 – 131 – 1500	131,3	103,5	128,0	68	42 / 64	116 / 164	240 / 420
T6 – 131 – 3000				99			
T6 - 146 – 1500	146,3	123,0	143,0	80	41 / 70	169 / 238	240 / 360
T6 – 146 – 3000				119			

Daten					Empfehlungen		
Typ	Bohr Ø mm	Kern Ø mm	Aussenrohr Ø mm	Gewicht Kernrohr Kg	Vorschubkraft kN	Wassermenge l/Min	Drehzahl U/Min
T6tr – 101 – 1500	101,3	76,0	98,2	48	31 / 48	65 / 92	280 / 540
T6tr – 101 – 3000				71			
T6tr – 116 – 1500	116,3	89,0	113,0	61	38 / 58	106 / 148	270 / 470
T6tr – 116 – 3000				88			
T6tr – 131 – 1500	131,3	103,5	128,0	70	44 / 67	113 / 160	240 / 410
T6tr – 131 – 3000				101			
T6tr - 146 – 1500	146,3	118,0	143,0	82	45 / 74	160 / 232	240 / 350
T6tr – 146 – 3000				122			

Daten					Empfehlungen		
Typ	Bohr Ø mm	Kern Ø mm	Aussenrohr Ø mm	Gewicht Kernrohr Kg	Vorschubkraft kN	Wassermenge l/Min	Drehzahl U/Min
T6S – 101 – 1500	101,3	72,0	98,2	47	30 / 45	67 / 94	330 / 570
T6S – 116 – 1500	116,3	86,0	113,0	60	37 / 55	108 / 152	300 / 480
T6S – 131 – 1500	131,3	100,8	128,0	69	42 / 64	116 / 164	240 / 420

Kernrohre T2 – T6 - T6tr Triple – T 6 S

Technische Daten und Empfehlungen

Diamant Kronen

Daten					Empfehlungen		
Typ	Bohr Ø mm	Kern Ø mm	Aussenrohr Ø mm	Gewicht Kernrohr Kg	Vorschubkraft kN	Wassermenge l/Min	Drehzahl U/Min
T2 – 46 - 1500	46,5	31,7	45,2	13	9 / 14	6 / 9	1250 / 1200
T2 – 46 – 3000				22			
T2 – 56 - 1500	56,5	41,7	55,2	14	11 / 17	7 / 11	1000 / 1700
T2 – 56 – 3000				23			
T2 – 66 – 1500	66,5	51,7	65,2	18	14 / 20	16 / 25	850 / 1450
T2 – 66 – 3000				29			
T2 – 76 – 1500	76,5	61,7	75,2	21	16 / 24	27 / 44	750 / 1250
T2 – 76 – 3000				34			
T2 – 86 – 1500	86,5	71,7	85,2	26	18 / 27	44 / 76	650 / 1100
T2 – 86 – 3000				41			
T2 – 101 – 1500	101,5	83,7	99,0	38	26 / 38	93 / 147	550 / 950
T2 – 101 – 3000				59			

Daten					Empfehlungen		
Typ	Bohr Ø mm	Kern Ø mm	Aussenrohr Ø mm	Gewicht Kernrohr Kg	Vorschubkraft kN	Wassermenge l/Min	Drehzahl U/Min
T6 – 101 – 1500	101,3	79,0	98,2	46	25 / 38	84 / 118	550 / 950
T6 – 101 – 3000				69			
T6 – 116 – 1500	116,3	93,0	113,0	59	31 / 46	136 / 190	500 / 800
T6 – 116 – 3000				86			
T6 – 131 – 1500	131,3	103,5	128,0	68	35 / 53	146 / 205	400 / 700
T6 – 131 – 3000				99			
T6 - 146 – 1500	146,3	123,0	143,0	80	34 / 59	212 / 297	400 / 600
T6 – 146 – 3000				119			

Daten					Empfehlungen		
Typ	Bohr Ø mm	Kern Ø mm	Aussenrohr Ø mm	Gewicht Kernrohr Kg	Vorschubkraft kN	Wassermenge l/Min	Drehzahl U/Min
T6tr – 101 – 1500	101,3	76,0	98,2	48	26 / 40	82 / 115	500 / 900
T6tr – 101 – 3000				71			
T6tr – 116 – 1500	116,3	89,0	113,0	61	32 / 48	133 / 185	450 / 780
T6tr – 116 – 3000				88			
T6tr – 131 – 1500	131,3	103,5	128,0	70	37 / 56	142 / 200	400 / 680
T6tr – 131 – 3000				101			
T6tr - 146 – 1500	146,3	118,0	143,0	82	38 / 62	200 / 290	400 / 580
T6tr – 146 – 3000				122			

Daten					Empfehlungen		
Typ	Bohr Ø mm	Kern Ø mm	Aussenrohr Ø mm	Gewicht Kernrohr Kg	Vorschubkraft kN	Wassermenge l/Min	Drehzahl U/Min
T6S – 101 – 1500	101,3	72,0	98,2	47	25 / 38	84 / 118	550 / 950
T6S – 116 – 1500	116,3	86,0	113,0	60	31 / 46	136 / 190	500 / 800
T6S – 131 – 1500	131,3	100,8	128,0	69	35 / 53	146 / 205	400 / 700